

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C

Version	Revision Date:	Date of last issue: 31.05.2019	Print Date:
3.1	05.12.2019	Date of first issue: 20.05.2016	06.12.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : WOLFRACOAT C
Article-No. : 099113

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Lubricant
stance/Mixture

Recommended restrictions : Restricted to professional users.
on use

1.3 Details of the supplier of the safety data sheet

Company : Klüber Lubrication München
Geisenhausenerstr. 7
81379 München
Deutschland
Tel: +49 (0) 89 7876 0
Fax: +49 (0) 89 7876 333
info@klueber.com

E-mail address of person : mcm@klueber.com
responsible for the SDS : Material Compliance Management

National contact : Klüber Lubrication Deutschland
Geisenhausenerstraße 7
81379 München
Deutschland
Tel.: +49 89 7876 0
Fax: +49 89 7876 565
customer.service.de@klueber.com
www.klueber.com

1.4 Emergency telephone number

Emergency telephone num- : +49 89 7876 700 (24 hrs)
ber

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Short-term (acute) aquatic hazard, Cate- H400: Very toxic to aquatic life.
gory 1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C

Version	Revision Date:	Date of last issue: 31.05.2019	Print Date:
3.1	05.12.2019	Date of first issue: 20.05.2016	06.12.2019

Long-term (chronic) aquatic hazard, Category 3 H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements :

Prevention:
P273 Avoid release to the environment.

Response:
P391 Collect spillage.

Additional Labelling

EUH208 Contains N,N-bis(2-ethylhexyl)-5-methyl-1H-benzotriazole-1-methylamine, N,N-bis(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methylamine, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-4-methyl-, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-5-methyl-, 1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-6-methyl-(Mixture)
. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Synthetic hydrocarbon oil
silicate
solid lubricant

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration limits M-Factor Notes	Concentration (% w/w)
copper	7440-50-8	Acute Tox.4; H302		>= 2,5 - < 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C

Version 3.1 Revision Date: 05.12.2019 Date of last issue: 31.05.2019 Print Date: 06.12.2019
 Date of first issue: 20.05.2016

	231-159-6 01-2119480154-42-XXXX	Aquatic Acute1; H400 Aquatic Chronic2; H411	M-Factor: 10/1	
Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]	800-362-7 01-2119974117-33-XXXX	Skin Irrit.2; H315 Eye Irrit.2; H319 STOT RE2; H373 Aquatic Acute1; H400 Aquatic Chronic2; H411	M-Factor: 10/1	>= 1 - < 2,5
N,N-bis(2-ethylhexyl)-5-methyl-1H-benzotriazole-1-methylamine, N,N-bis(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methylamine, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-4-methyl-, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-5-methyl-, 1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-6-methyl-(Mixture)	939-700-4 01-2119982395-25-XXXX	Skin Irrit.2; H315 Skin Sens.1B; H317 Aquatic Acute1; H400 Aquatic Chronic2; H411	M-Factor: 1/1	>= 0,1 - < 0,25
Substances with a workplace exposure limit :				
Graphite	7782-42-5 231-955-3 01-2119486977-12-XXXX	Not classified		>= 1 - < 10
titanium dioxide	13463-67-7 236-675-5 01-2119489379-17-XXXX	Not classified		>= 1 - < 10
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1 01-2119529243-45-XXXX	Flam. Sol.1; H228		>= 1 - < 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



WOLFRACOAT C

Version	Revision Date:	Date of last issue: 31.05.2019	Print Date:
3.1	05.12.2019	Date of first issue: 20.05.2016	06.12.2019

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash off immediately with soap and plenty of water.
Get medical attention immediately if irritation develops and persists.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
If eye irritation persists, consult a specialist.
- If swallowed : Move the victim to fresh air.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
Do not induce vomiting without medical advice.
Obtain medical attention.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No information available.
- Risks : None known.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



WOLFRACOAT C

Version	Revision Date:	Date of last issue: 31.05.2019	Print Date:
3.1	05.12.2019	Date of first issue: 20.05.2016	06.12.2019

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Fire may cause evolution of:
Carbon oxides
Metal oxides
Nitrogen oxides (NOx)

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).
Do not breathe vapours, aerosols.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Clean up promptly by sweeping or vacuum.
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



WOLFRACOAT C

Version	Revision Date:	Date of last issue: 31.05.2019	Print Date:
3.1	05.12.2019	Date of first issue: 20.05.2016	06.12.2019

Advice on safe handling : Do not breathe vapours or spray mist.
Avoid contact with skin and eyes.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after handling the product.
Do not get in eyes or mouth or on skin.
Do not get on skin or clothing.
Do not ingest.
Do not repack.
Do not re-use empty containers.
These safety instructions also apply to empty packaging which may still contain product residues.
Keep container closed when not in use.
Avoid inhalation of vapour or mist.

Do not use in areas without adequate ventilation.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after handling the product.
Do not get in eyes or mouth or on skin.
Do not get on skin or clothing.
Do not ingest.
Do not repack.
These safety instructions also apply to empty packaging which may still contain product residues.
Keep container closed when not in use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep container closed when not in use. Keep in a dry, cool and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with the particular national regulations. Keep in properly labelled containers.

Storage class (TRGS 510) : 11, Combustible Solids

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



WOLFRACOAT C

Version 3.1 Revision Date: 05.12.2019 Date of last issue: 31.05.2019 Print Date: 06.12.2019
Date of first issue: 20.05.2016

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Graphite	7782-42-5	AGW (Inhalable fraction)	10 mg/m ³	DE TRGS 900 (2014-04-02)
Peak-limit: excursion factor (category)	2;(II)			
Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
		AGW (Alveolate fraction)	1,25 mg/m ³	DE TRGS 900 (2014-04-02)
Peak-limit: excursion factor (category)	2;(II)			
Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
aluminium powder (stabilised)	7429-90-5	AGW (Inhalable fraction)	10 mg/m ³	DE TRGS 900 (2014-04-02)
Peak-limit: excursion factor (category)	2;(II)			
Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
		AGW (Alveolate fraction)	1,25 mg/m ³	DE TRGS 900 (2014-04-02)
Peak-limit: excursion factor (category)	2;(II)			
Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values.,			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C

Version
3.1

Revision Date:
05.12.2019

Date of last issue: 31.05.2019
Date of first issue: 20.05.2016

Print Date:
06.12.2019

	Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
Graphite	7782-42-5	AGW (Inhalable fraction)	10 mg/m ³	DE TRGS 900 (2014-04-02)
Peak-limit: excursion factor (category)	2;(II)			
Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
		AGW (Alveolate fraction)	1,25 mg/m ³	DE TRGS 900 (2014-04-02)
Peak-limit: excursion factor (category)	2;(II)			
Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
titanium dioxide	13463-67-7	AGW (Inhalable fraction)	10 mg/m ³ (Titanium dioxide)	DE TRGS 900 (2014-04-02)
Peak-limit: excursion factor (category)	2;(II)			
Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
		AGW (Alveolate fraction)	1,25 mg/m ³ (Titanium dioxide)	DE TRGS 900 (2014-04-02)
Peak-limit: excursion factor (category)	2;(II)			
Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
aluminium powder (stabilised)	7429-90-5	AGW (Inhalable fraction)	10 mg/m ³	DE TRGS 900 (2014-04-02)
Peak-limit: excursion factor (category)	2;(II)			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C

Version
3.1

Revision Date:
05.12.2019

Date of last issue: 31.05.2019
Date of first issue: 20.05.2016

Print Date:
06.12.2019

Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
		AGW (Alveolate fraction)	1,25 mg/m3	DE TRGS 900 (2014-04-02)
Peak-limit: excursion factor (category)	2;(II)			
Further information	General dust value. For this substance no specific occupational exposure limit value is established, since the AGS does not yet have information regarding unspecific action on the respiratory organs in excess of the normal values., Commission for dangerous substances, Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Benzene, mono-C10-13-alkyl derivs., distr. residues	Workers	Inhalation	Long-term systemic effects	3,2 mg/m3
	Workers	Skin contact	Long-term systemic effects	4,3 mg/kg bw/day
copper	Workers	Inhalation	Long-term systemic effects	20 mg/m3
	Workers	Skin contact	Long-term systemic effects	137 mg/kg
	Workers	Skin contact	Acute systemic effects	237 mg/kg
Graphite	Workers	Inhalation	Long-term systemic effects	1,2 mg/m3
titanium dioxide	Workers	Inhalation	Long-term local effects	10 mg/m3
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3,72 mg/m3
	Workers	Inhalation	Long-term local effects	3,72 mg/m3
Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]	Workers	Skin contact	Long-term systemic effects	0,04 mg/kg
	Workers	Inhalation	Long-term systemic effects	0,29 mg/m3
N,N-bis(2-ethylhexyl)-5-methyl-1H-benzotriazole-1-methylamine, N,N-bis(2-ethylhexyl)-4-	Industrial use	Inhalation	Long-term systemic effects	1,3 mg/m3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C

Version 3.1 Revision Date: 05.12.2019 Date of last issue: 31.05.2019 Print Date: 06.12.2019
 Date of first issue: 20.05.2016

methyl-1H-benzotriazole-1-methylamine, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-4-methyl-, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-5-methyl-, 1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-6-methyl-(Mixture)				
	Industrial use	Skin contact	Long-term systemic effects	0,4 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Benzene, mono-C10-13-alkyl derivs., distn. residues	Fresh water	0,001 mg/l
	Intermittent use/release	0,001 mg/l
	Marine water	0 mg/l
	Microbiological Activity in Sewage Treatment Systems	2 mg/l
	Fresh water sediment	1,65 mg/kg
	Marine sediment	0,165 mg/kg
	Soil	0,329 mg/kg
copper	Fresh water	0,0078 mg/l
	Marine water	0,0052 mg/l
	Sewage treatment plant	0,230 mg/l
	Fresh water sediment	87 mg/kg
	Marine sediment	676 mg/kg
titanium dioxide	Soil	65 mg/kg
	Fresh water	0,184 mg/l
	Intermittent use/release	0,193 mg/l
	Marine water	0,0184 mg/l
	Sewage treatment plant	100 mg/l
aluminium powder (stabilised)	Marine sediment	100 mg/l
	Fresh water sediment	1000 mg/l
	Soil	100 mg/l
	Fresh water	0,0749 mg/l
	Sewage treatment plant	20 mg/l
Amines, N-C16-C18-alkyl- (evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]	Fresh water	0,00638 mg/l
	Marine water	0,000638 mg/l
	Intermittent use/release	0,00509 mg/l
	Microbiological Activity in Sewage Treat-	98,6 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C

Version 3.1 Revision Date: 05.12.2019 Date of last issue: 31.05.2019 Print Date: 06.12.2019
Date of first issue: 20.05.2016

	ment Systems	
	Fresh water sediment	204 mg/kg
	Marine sediment	20,4 mg/kg
	Soil	9,93 mg/kg
N,N-bis(2-ethylhexyl)-5-methyl-1H-benzotriazole-1-methylamine, N,N-bis(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methylamine, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-4-methyl-, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-5-methyl-, 1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-6-methyl-(Mixture)	Fresh water	0,000976 mg/l
	Marine water	0,000098 mg/l
	Intermittent use/release	0,00976 mg/l
	Soil	0,00184 - 0,842 mg/kg
	Fresh water sediment	0,0121 - 4,23 mg/kg
	Marine sediment	0,00121 - 0,423 mg/kg
	Microbiological Activity in Sewage Treatment Systems	0,69 mg/l

8.2 Exposure controls

Engineering measures

none

Personal protective equipment

Eye protection : Tightly fitting safety goggles

Hand protection

Material : Nitrile rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.
The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Respiratory protection : Not required; except in case of aerosol formation.

Filter type : Filter type P

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C

Version	Revision Date:	Date of last issue: 31.05.2019	Print Date:
3.1	05.12.2019	Date of first issue: 20.05.2016	06.12.2019

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: paste
Colour	: grey
Odour	: characteristic
Odour Threshold	: No data available
pH	: Not applicable
Melting point/range	: No data available
Boiling point/boiling range	: No data available
Flash point	: Not applicable
Evaporation rate	: No data available
Flammability (solid, gas)	: Combustible Solids, Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: < 0,001 hPa (20 °C)
Relative vapour density	: No data available
Density	: 1,01 g/cm ³ (20 °C)
Bulk density	: No data available
Solubility(ies) Water solubility	: insoluble

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C

Version	Revision Date:	Date of last issue: 31.05.2019	Print Date:
3.1	05.12.2019	Date of first issue: 20.05.2016	06.12.2019

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

 Viscosity, dynamic : No data available

 Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : No data available

9.2 Other information

Sublimation point : No data available

Self-ignition : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : No conditions to be specially mentioned.

10.5 Incompatible materials

Materials to avoid : No materials to be especially mentioned.

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C

Version	Revision Date:	Date of last issue: 31.05.2019	Print Date:
3.1	05.12.2019	Date of first issue: 20.05.2016	06.12.2019

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Remarks: This information is not available.

Acute dermal toxicity : Remarks: This information is not available.

Components:

copper:

Acute oral toxicity : LD50 (Rat): 482 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 5,11 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 436
GLP: yes
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
GLP: yes
Assessment: The substance or mixture has no acute dermal toxicity

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

N,N-bis(2-ethylhexyl)-5-methyl-1H-benzotriazole-1-methylamine, N,N-bis(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methylamine, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-4-methyl-, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-5-methyl-, 1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-6-methyl-(Mixture)

:
Acute oral toxicity : LD50 (Rat): 3.313 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



WOLFRACOAT C

Version	Revision Date:	Date of last issue: 31.05.2019	Print Date:
3.1	05.12.2019	Date of first issue: 20.05.2016	06.12.2019

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Graphite:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 423
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 2.000 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

titanium dioxide:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : (Rat): > 5,09 mg/l
Method: OECD Test Guideline 403
GLP: no

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5,09 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Skin corrosion/irritation

Product:

Remarks : This information is not available.

Components:

copper:

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C

Version	Revision Date:	Date of last issue: 31.05.2019	Print Date:
3.1	05.12.2019	Date of first issue: 20.05.2016	06.12.2019

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Species : Rabbit
Assessment : Irritating to skin.
Result : Irritating to skin.

N,N-bis(2-ethylhexyl)-5-methyl-1H-benzotriazole-1-methylamine, N,N-bis(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methylamine, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-4-methyl-, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-5-methyl-, 1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-6-methyl-(Mixture)

:
Species : Rabbit
Assessment : Irritating to skin.
Method : Draize Test
Result : Irritating to skin.

Graphite:

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation

titanium dioxide:

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : no

aluminium powder (stabilised):

Species : Rabbit
Assessment : No skin irritation
Result : No skin irritation

Serious eye damage/eye irritation

Product:

Remarks : This information is not available.

Components:

copper:

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C

Version	Revision Date:	Date of last issue: 31.05.2019	Print Date:
3.1	05.12.2019	Date of first issue: 20.05.2016	06.12.2019

GLP : yes

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Species : Rabbit
Assessment : Irritating to eyes.
Method : OECD Test Guideline 405
Result : Irritating to eyes.

N,N-bis(2-ethylhexyl)-5-methyl-1H-benzotriazole-1-methylamine, N,N-bis(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methylamine, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-4-methyl-, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-5-methyl-, 1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-6-methyl-(Mixture)

:
Species : Rabbit
Assessment : No eye irritation
Method : Draize Test
Result : No eye irritation

Graphite:

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation

titanium dioxide:

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation

aluminium powder (stabilised):

Species : Rabbit
Assessment : No eye irritation
Result : No eye irritation

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

copper:

Test Type : Maximisation Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



WOLFRACOAT C

Version	Revision Date:	Date of last issue: 31.05.2019	Print Date:
3.1	05.12.2019	Date of first issue: 20.05.2016	06.12.2019

Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.
GLP : yes

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Assessment : Does not cause skin sensitisation.
Result : Does not cause skin sensitisation.

N,N-bis(2-ethylhexyl)-5-methyl-1H-benzotriazole-1-methylamine, N,N-bis(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methylamine, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-4-methyl-, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-5-methyl-, 1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-6-methyl-(Mixture)

:

Test Type : Maximisation Test
Species : Guinea pig
Assessment : The product is a skin sensitiser, sub-category 1B.
Method : OECD Test Guideline 406
Result : The product is a skin sensitiser, sub-category 1B.

Graphite:

Species : Mouse
Method : OECD Test Guideline 429
Result : negative

titanium dioxide:

Species : Mouse
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 429
Result : Does not cause skin sensitisation.

aluminium powder (stabilised):

Species : Guinea pig
Assessment : Did not cause sensitisation on laboratory animals.
Result : Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available
Genotoxicity in vivo : Remarks: No data available

Components:

copper:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



WOLFRACOAT C

Version	Revision Date:	Date of last issue: 31.05.2019	Print Date:
3.1	05.12.2019	Date of first issue: 20.05.2016	06.12.2019

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Genotoxicity in vitro : Test Type: Ames test
Result: negative

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

N,N-bis(2-ethylhexyl)-5-methyl-1H-benzotriazole-1-methylamine, N,N-bis(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methylamine, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-4-methyl-, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-5-methyl-, 1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-6-methyl-(Mixture)

:

Genotoxicity in vitro : Test Type: Ames test
Method: OECD Test Guideline 471
Result: negative

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Graphite:

Genotoxicity in vitro : Test Type: Microbial mutagenesis assay (Ames test)
Method: OECD Test Guideline 471
Result: negative

Test Type: gene mutation test
Method: OECD Test Guideline 476
Result: negative

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

titanium dioxide:

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Carcinogenicity

Product:

Remarks : No data available

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



WOLFRACOAT C

Version	Revision Date:	Date of last issue: 31.05.2019	Print Date:
3.1	05.12.2019	Date of first issue: 20.05.2016	06.12.2019

Components:

copper:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

N,N-bis(2-ethylhexyl)-5-methyl-1H-benzotriazole-1-methylamine, N,N-bis(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methylamine, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-4-methyl-, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-5-methyl-, 1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-6-methyl-(Mixture)

:

Carcinogenicity - Assessment : Carcinogenicity classification not possible from current data.

titanium dioxide:

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

Components:

copper:

Reproductive toxicity - Assessment : No toxicity to reproduction
No toxicity to reproduction

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Reproductive toxicity - Assessment : No toxicity to reproduction
No toxicity to reproduction

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C

Version	Revision Date:	Date of last issue: 31.05.2019	Print Date:
3.1	05.12.2019	Date of first issue: 20.05.2016	06.12.2019

N,N-bis(2-ethylhexyl)-5-methyl-1H-benzotriazole-1-methylamine, N,N-bis(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methylamine, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-4-methyl-, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-5-methyl-, 1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-6-methyl-(Mixture)

:

Effects on fertility : Species: Rat
Application Route: Oral
General Toxicity - Parent: NOAEL: 45 mg/kg body weight
General Toxicity F1: NOAEL: 45 mg/kg body weight
Fertility: NOAEL: 150 mg/kg body weight
Method: OECD Test Guideline 422

Effects on foetal development : Species: Rat
Application Route: Oral
Duration of Single Treatment: 28 h
General Toxicity Maternal: NOAEL: 45 mg/kg body weight
Developmental Toxicity: NOAEL: 45 mg/kg body weight
Method: OECD Test Guideline 422

Reproductive toxicity - Assessment : No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.
No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

Graphite:

Effects on fertility : Species: Rat
Application Route: Oral
General Toxicity F1: NOAEL: 813 mg/kg body weight
Method: OECD Test Guideline 422

titanium dioxide:

Reproductive toxicity - Assessment : No toxicity to reproduction
No effects on or via lactation

STOT - single exposure

Components:

copper:

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

N,N-bis(2-ethylhexyl)-5-methyl-1H-benzotriazole-1-methylamine, N,N-bis(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methylamine, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-4-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C

Version	Revision Date:	Date of last issue: 31.05.2019	Print Date:
3.1	05.12.2019	Date of first issue: 20.05.2016	06.12.2019

methyl-, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-5-methyl-, 1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-6-methyl-(Mixture)

:

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

titanium dioxide:

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure

Components:

copper:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Exposure routes : Ingestion

Assessment : May cause damage to organs through prolonged or repeated exposure.

N,N-bis(2-ethylhexyl)-5-methyl-1H-benzotriazole-1-methylamine, N,N-bis(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methylamine, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-4-methyl-, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-5-methyl-, 1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-6-methyl-(Mixture)

:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

titanium dioxide:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity

Product:

Remarks : This information is not available.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C

Version	Revision Date:	Date of last issue: 31.05.2019	Print Date:
3.1	05.12.2019	Date of first issue: 20.05.2016	06.12.2019

Components:

N,N-bis(2-ethylhexyl)-5-methyl-1H-benzotriazole-1-methylamine, N,N-bis(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methylamine, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-4-methyl-, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-5-methyl-, 1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-6-methyl-(Mixture)

:

Species	:	Rat
NOAEL	:	45 mg/kg
Application Route	:	Oral
Exposure time	:	28
Method	:	OECD Test Guideline 422

Graphite:

Species	:	Rat
NOAEL	:	813 mg/kg
Application Route	:	Oral
Method	:	OECD Test Guideline 422

Species	:	Rat
NOAEL	:	> 2 mg/l
Application Route	:	inhalation (dust/mist/fume)
Method	:	OECD Test Guideline 412

Aspiration toxicity

Product:

This information is not available.

Components:

copper:

No aspiration toxicity classification

N,N-bis(2-ethylhexyl)-5-methyl-1H-benzotriazole-1-methylamine, N,N-bis(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methylamine, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-4-methyl-, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-5-methyl-, 1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-6-methyl-(Mixture)

:

No aspiration toxicity classification

titanium dioxide:

No aspiration toxicity classification

Further information

Product:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



WOLFRACOAT C

Version 3.1	Revision Date: 05.12.2019	Date of last issue: 31.05.2019 Date of first issue: 20.05.2016	Print Date: 06.12.2019
----------------	------------------------------	---	---------------------------

Remarks : Information given is based on data on the components and the toxicology of similar products.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: Very toxic to aquatic organisms.

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms :
Remarks: No data available

Components:

copper:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0,094 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,0338 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 37,6 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 10

Toxicity to fish (Chronic toxicity) : NOEC: 0,021 mg/l
Exposure time: 27 d

M-Factor (Chronic aquatic toxicity) : 1

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C

Version	Revision Date:	Date of last issue: 31.05.2019	Print Date:
3.1	05.12.2019	Date of first issue: 20.05.2016	06.12.2019

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 0,1 - 1 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 0,1 - 1 mg/l
Exposure time: 48 h
- Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 0,01 - 0,1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- M-Factor (Acute aquatic toxicity) : 10
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC50: 1,41 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Method: OECD Test Guideline 211
- M-Factor (Chronic aquatic toxicity) : 1

Ecotoxicology Assessment

- Acute aquatic toxicity : Very toxic to aquatic life.
- Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

N,N-bis(2-ethylhexyl)-5-methyl-1H-benzotriazole-1-methylamine, N,N-bis(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methylamine, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-4-methyl-, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-5-methyl-, 1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-6-methyl-(Mixture)

- :
- Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): 1,3 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2,05 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 0,762 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C

Version	Revision Date:	Date of last issue: 31.05.2019	Print Date:
3.1	05.12.2019	Date of first issue: 20.05.2016	06.12.2019

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : EC20 (activated sludge): 15 mg/l
Exposure time: 3 h
Test Type: Respiration inhibition
Method: OECD Test Guideline 209

M-Factor (Chronic aquatic toxicity) : 1

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Graphite:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

titanium dioxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202

aluminium powder (stabilised):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0,12 mg/l
Exposure time: 96 h
Test Type: static test
Remarks: No toxicity at the limit of solubility

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C

Version	Revision Date:	Date of last issue: 31.05.2019	Print Date:
3.1	05.12.2019	Date of first issue: 20.05.2016	06.12.2019

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

Components:

copper:

Biodegradability : Remarks: The methods for determining biodegradability are not applicable to inorganic substances.

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: rapidly biodegradable
Biodegradation: 65 %
Exposure time: 28 d
Method: OECD Test Guideline 301D
GLP: yes

N,N-bis(2-ethylhexyl)-5-methyl-1H-benzotriazole-1-methylamine, N,N-bis(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methylamine, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-4-methyl-, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-5-methyl-, 1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-6-methyl-(Mixture)

:

Biodegradability : Test Type: Primary biodegradation
Inoculum: activated sludge
Result: Not rapidly biodegradable
Biodegradation: < 10 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Graphite:

Biodegradability : Remarks: The methods for determining biodegradability are not applicable to inorganic substances.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



WOLFRACOAT C

Version	Revision Date:	Date of last issue: 31.05.2019	Print Date:
3.1	05.12.2019	Date of first issue: 20.05.2016	06.12.2019

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

Components:

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

N,N-bis(2-ethylhexyl)-5-methyl-1H-benzotriazole-1-methylamine, N,N-bis(2-ethylhexyl)-4-methyl-1H-benzotriazole-1-methylamine, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-4-methyl-, 2H-Benzotriazole-2-methanamine, N,N-bis(2-ethylhexyl)-5-methyl-, 1H-Benzotriazole-1-methanamine, N,N-bis(2-ethylhexyl)-6-methyl-(Mixture)

:

Bioaccumulation : Bioconcentration factor (BCF): 1.676

Partition coefficient: n-octanol/water : Remarks: Not applicable

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

Components:

copper:

Assessment : Remarks: Not applicable

titanium dioxide:

Assessment : Non-classified vPvB substance. Non-classified PBT substance.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



WOLFRACOAT C

Version 3.1	Revision Date: 05.12.2019	Date of last issue: 31.05.2019 Date of first issue: 20.05.2016	Print Date: 06.12.2019
----------------	------------------------------	---	---------------------------

12.6 Other adverse effects

Product:

Additional ecological information : Very toxic to aquatic life.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and national regulations.

Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Dispose of waste product or used containers according to local regulations.

The following Waste Codes are only suggestions:

SECTION 14: Transport information

14.1 UN number

ADR : UN 3077

IMDG : UN 3077

IATA : UN 3077

14.2 UN proper shipping name

ADR : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Tallow aminoleate, Copper metal powder)

IMDG : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
(Tallow aminoleate, Copper metal powder)

IATA : Environmentally hazardous substance, solid, n.o.s.
(Tallow aminoleate, Copper metal powder)

14.3 Transport hazard class(es)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C

Version	Revision Date:	Date of last issue: 31.05.2019	Print Date:
3.1	05.12.2019	Date of first issue: 20.05.2016	06.12.2019

ADR : 9
IMDG : 9
IATA : 9

14.4 Packing group

ADR

Packing group : III
Classification Code : M7
Hazard Identification Number : 90
Labels : 9

IMDG

Packing group : III
Labels : 9
EmS Code : F-A, S-F

IATA (Cargo)

Packing instruction (cargo aircraft) : 956
Packing instruction (LQ) : Y956
Packing group : III
Labels : Class 9 - Miscellaneous dangerous substances and articles

IATA (Passenger)

Packing instruction (passenger aircraft) : 956
Packing instruction (LQ) : Y956
Packing group : III
Labels : Class 9 - Miscellaneous dangerous substances and articles

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C

Version	Revision Date:	Date of last issue: 31.05.2019	Print Date:
3.1	05.12.2019	Date of first issue: 20.05.2016	06.12.2019

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).
- REACH - List of substances subject to authorisation (Annex XIV) : Not applicable
- Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable
- Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable
- Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable
- REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E1 ENVIRONMENTAL HAZARDS

E1

Water contaminating class (Germany) : WGK 3 highly hazardous to water
Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : Total dust:
others: 21,47 %

Inorganic substances in powdered form:
portion Class 3: 8 %

Inorganic substances in vapour or gaseous form:
Not applicable
Organic Substances:
others: 70,53 %

Carcinogenic substances:
Not applicable
Mutagenic:
Not applicable
Toxic to reproduction:
Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



WOLFRACOAT C

Version	Revision Date:	Date of last issue: 31.05.2019	Print Date:
3.1	05.12.2019	Date of first issue: 20.05.2016	06.12.2019

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Not applicable

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

H228 : Flammable solid.
H302 : Harmful if swallowed.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.
H373 : May cause damage to organs through prolonged or repeated exposure if swallowed.
H400 : Very toxic to aquatic life.
H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



WOLFRACOAT C

Version	Revision Date:	Date of last issue: 31.05.2019	Print Date:
3.1	05.12.2019	Date of first issue: 20.05.2016	06.12.2019

Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Aquatic Acute 1 H400

Aquatic Chronic 3 H412

Classification procedure:

Calculation method

Calculation method

This safety data sheet applies only to products originally packed and labelled by KLÜBER LUBRICATION. The information contained therein may not be reproduced or modified without the express written permission of KLÜBER LUBRICATION. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of our safety data sheets (e.g. as a document for download from the Internet) is not permitted without the express written consent of KLÜBER LUBRICATION. KLÜBER LUBRICATION provides its customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. KLÜBER LUBRICATION provides no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorised trading partner of KLÜBER LUBRICATION.