

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



WOLFRACOAT C Spray

Version	Revision Date:	Date of last issue: 03.04.2019	Print Date:
7.0	18.12.2019	Date of first issue: 26.05.2015	18.12.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : WOLFRACOAT C Spray
Article-No. : 081150

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Lubricant spray
Recommended restrictions on use : Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : Klüber Lubrication München
Geisenhausenerstr. 7
81379 München
Deutschland
Tel: +49 (0) 89 7876 0
Fax: +49 (0) 89 7876 333
info@klueber.com

E-mail address of person responsible for the SDS : mcm@klueber.com
Material Compliance Management

National contact : Klüber Lubrication Deutschland
Geisenhausenerstraße 7
81379 München
Deutschland
Tel.: +49 89 7876 0
Fax: +49 89 7876 565
customer.service.de@klueber.com
www.klueber.com

1.4 Emergency telephone number

Emergency telephone number : +49 89 7876 700 (24 hrs)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.
H229: Pressurised container: May burst if heated.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION


WOLFRACOAT C Spray

Version	Revision Date:	Date of last issue: 03.04.2019	Print Date:
7.0	18.12.2019	Date of first issue: 26.05.2015	18.12.2019

Skin irritation, Category 2	H315: Causes skin irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P273 Avoid release to the environment. Response: P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331 Do NOT induce vomiting. P391 Collect spillage. Storage: P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Hydrocarbons, C7-C9, isoalkanes

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C Spray

Version	Revision Date:	Date of last issue: 03.04.2019	Print Date:
7.0	18.12.2019	Date of first issue: 26.05.2015	18.12.2019

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Propellant
solvent (hydrocarbons)
Synthetic hydrocarbon oil
silicate
solid lubricant

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration limits M-Factor Notes	Concentration (% w/w)
Hydrocarbons, C7-C9, isoalkanes	921-728-3 01-2119471305-42- XXXX	Flam. Liq.2; H225 Skin Irrit.2; H315 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411	Note P	>= 20 - < 25
copper	7440-50-8 231-159-6 01-2119480154-42- XXXX	Acute Tox.4; H302 Aquatic Acute1; H400 Aquatic Chronic2; H411	M-Factor: 10/1	>= 1 - < 2,5
Amines, N-C16-C18- alkyl-(evennumbered, C18 unsaturated) propane-1,3- diaminium di[(9Z)- octadec-9-enoate]	800-362-7 01-2119974117-33- XXXX	Skin Irrit.2; H315 Eye Irrit.2; H319 STOT RE2; H373 Aquatic Acute1; H400 Aquatic Chronic2; H411	M-Factor: 10/1	>= 0,1 - < 0,25
Substances with a workplace exposure limit :				
isobutane	75-28-5 200-857-2 601-004-00-0 01-2119485395-27- XXXX	Flam. Gas1; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	>= 30 - < 50
propane	74-98-6 200-827-9	Flam. Gas1; H220 Press. GasCompr.		>= 1 - < 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



WOLFRACOAT C Spray

Version 7.0 Revision Date: 18.12.2019 Date of last issue: 03.04.2019 Print Date: 18.12.2019
Date of first issue: 26.05.2015

	601-003-00-5 01-2119486944-21-XXXX	Gas; H280	Note U (table 3.1)	
butane	106-97-8 203-448-7 601-004-00-0 01-2119474691-32-XXXX	Flam. Gas1; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	$\geq 1 - < 10$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- If inhaled : Call a physician or poison control centre immediately.
Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash off immediately with soap and plenty of water.
Get medical attention immediately if irritation develops and persists.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
If eye irritation persists, consult a specialist.
- If swallowed : Move the victim to fresh air.
If accidentally swallowed obtain immediate medical attention.
Keep respiratory tract clear.
Do NOT induce vomiting.
Rinse mouth with water.
Aspiration hazard if swallowed - can enter lungs and cause damage.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Inhalation may provoke the following symptoms:
Unconsciousness

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C Spray

Version	Revision Date:	Date of last issue: 03.04.2019	Print Date:
7.0	18.12.2019	Date of first issue: 26.05.2015	18.12.2019

Dizziness
Drowsiness
Headache
Nausea
Tiredness
Skin contact may provoke the following symptoms:
Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

Risks : Central nervous system depression
Risk of product entering the lungs on vomiting after ingestion.
Health injuries may be delayed.
Causes skin irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Fire may cause evolution of:
Carbon oxides
Metal oxides
Nitrogen oxides (NO_x)

Fire Hazard
Do not let product enter drains.
Contains gas under pressure; may explode if heated.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Cool containers/tanks with water spray.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C Spray

Version	Revision Date:	Date of last issue: 03.04.2019	Print Date:
7.0	18.12.2019	Date of first issue: 26.05.2015	18.12.2019

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Ensure adequate ventilation.
Remove all sources of ignition.
Do not breathe vapours or spray mist.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Refer to protective measures listed in sections 7 and 8.
Only qualified personnel equipped with suitable protective equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.
Non-sparking tools should be used.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not use in areas without adequate ventilation.
Do not breathe vapours or spray mist.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin and eyes.
For personal protection see section 8.
Keep away from fire, sparks and heated surfaces.
Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after handling the product.
Do not get in eyes or mouth or on skin.
Do not get on skin or clothing.
Do not ingest.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



WOLFRACOAT C Spray

Version	Revision Date:	Date of last issue: 03.04.2019	Print Date:
7.0	18.12.2019	Date of first issue: 26.05.2015	18.12.2019

Do not use sparking tools.
These safety instructions also apply to empty packaging which may still contain product residues.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular national regulations.

Storage class (TRGS 510) : 2B, Aerosol cans and lighters

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
isobutane	75-28-5	AGW	1.000 ppm 2.400 mg/m ³	DE TRGS 900 (2006-01-01)
Peak-limit: excursion factor (category)	4;(II)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
Hydrocarbons, C7-C9, isoalkanes	Not Assigned	AGW	1.500 mg/m ³	DE TRGS 900 (2009-02-16)
Peak-limit: excursion factor (category)	2;(II)			
Further information	Group exposure limit for hydrocarbon solvent mixtures, Commission for dangerous substances, See also No. 2.9 of the TRGS 900			
		AGW	600 mg/m ³	DE TRGS 900 (2009-02-16)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C Spray

Version 7.0 Revision Date: 18.12.2019 Date of last issue: 03.04.2019
Date of first issue: 26.05.2015

Print Date:
18.12.2019

Peak-limit: excursion factor (category)	2;(II)			
Further information	Group exposure limit for hydrocarbon solvent mixtures, Commission for dangerous substances, See also No. 2.9 of the TRGS 900			
propane	74-98-6	AGW	1.000 ppm 1.800 mg/m ³	DE TRGS 900 (2006-01-01)
Peak-limit: excursion factor (category)	4;(II)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			
butane	106-97-8	AGW	1.000 ppm 2.400 mg/m ³	DE TRGS 900 (2006-01-01)
Peak-limit: excursion factor (category)	4;(II)			
Further information	Senate commission for the review of compounds at the work place dangerous for the health (MAK-commission).			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Hydrocarbons, C7-C9, isoalkanes	Workers	Inhalation	Long-term systemic effects	2035 mg/m ³
	Workers	Dermal	Long-term systemic effects	773 mg/kg bw/day
Benzene, mono-C10-13-alkyl derivs., distn. residues	Workers	Inhalation	Long-term systemic effects	3,2 mg/m ³
	Workers	Skin contact	Long-term systemic effects	4,3 mg/kg bw/day
copper	Workers	Inhalation	Long-term systemic effects	20 mg/m ³
	Workers	Skin contact	Long-term systemic effects	137 mg/kg
	Workers	Skin contact	Acute systemic effects	237 mg/kg
Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]	Workers	Skin contact	Long-term systemic effects	0,04 mg/kg
	Workers	Inhalation	Long-term systemic effects	0,29 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Benzene, mono-C10-13-alkyl	Fresh water	0,001 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C Spray

Version 7.0 Revision Date: 18.12.2019 Date of last issue: 03.04.2019
Date of first issue: 26.05.2015

Print Date:
18.12.2019

derivs., distn. residues		
	Intermittent use/release	0,001 mg/l
	Marine water	0 mg/l
	Microbiological Activity in Sewage Treatment Systems	2 mg/l
	Fresh water sediment	1,65 mg/kg
	Marine sediment	0,165 mg/kg
	Soil	0,329 mg/kg
copper	Fresh water	0,0078 mg/l
	Marine water	0,0052 mg/l
	Sewage treatment plant	0,230 mg/l
	Fresh water sediment	87 mg/kg
	Marine sediment	676 mg/kg
	Soil	65 mg/kg
Amines, N-C16-C18-alkyl- (evennumbered, C18 unsaturated) propane-1,3-diaminium dij(9Z)-octadec-9-enoate]	Fresh water	0,00638 mg/l
	Marine water	0,000638 mg/l
	Intermittent use/release	0,00509 mg/l
	Microbiological Activity in Sewage Treatment Systems	98,6 mg/l
	Fresh water sediment	204 mg/kg
	Marine sediment	20,4 mg/kg
	Soil	9,93 mg/kg

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye protection : Safety glasses with side-shields

Hand protection

Material : Nitrile rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.
The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Short term only

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



WOLFRACOAT C Spray

Version	Revision Date:	Date of last issue: 03.04.2019	Print Date:
7.0	18.12.2019	Date of first issue: 26.05.2015	18.12.2019

Filter type : Filter type A-P

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : aerosol

Colour : grey

Odour : characteristic

Odour Threshold : No data available

Values refer to the propellant:

pH : No data available

Melting point/range : No data available

Boiling point/boiling range : < -10 °C

Flash point : -80 °C
Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : 11,2 %(V)

Lower explosion limit / Lower flammability limit : 1,5 %(V)

Vapour pressure : 2.700 hPa (20 °C)

Relative vapour density : No data available

Density : 0,60 g/cm³
(20 °C)

Bulk density : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C Spray

Version	Revision Date:	Date of last issue: 03.04.2019	Print Date:
7.0	18.12.2019	Date of first issue: 26.05.2015	18.12.2019

Solubility(ies)
Water solubility : < 0,1 g/l insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : > 350 °C

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : No data available

9.2 Other information

Sublimation point : No data available

Self-ignition : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C Spray

Version	Revision Date:	Date of last issue: 03.04.2019	Print Date:
7.0	18.12.2019	Date of first issue: 26.05.2015	18.12.2019

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

- Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method
- Remarks: Effects due to ingestion may include:
- Symptoms: Central nervous system depression
- Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.
- Symptoms: Inhalation may provoke the following symptoms:,
Respiratory disorder, Dizziness, Drowsiness, Vomiting, Fa-
tigue, Vertigo, Central nervous system depression
- Acute dermal toxicity : Symptoms: Redness, Local irritation

Components:

Hydrocarbons, C7-C9, isoalkanes:

- Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401
- Acute inhalation toxicity : LC50 (Rat): > 21 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhala-
tion toxicity
- Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal
toxicity

copper:

- Acute oral toxicity : LD50 (Rat): 482 mg/kg
Method: OECD Test Guideline 401
GLP: yes
- Acute inhalation toxicity : LC50 (Rat): > 5,11 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 436
GLP: yes
Assessment: The substance or mixture has no acute inhala-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C Spray

Version	Revision Date:	Date of last issue: 03.04.2019	Print Date:
7.0	18.12.2019	Date of first issue: 26.05.2015	18.12.2019

tion toxicity

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402
GLP: yes
Assessment: The substance or mixture has no acute dermal toxicity

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

isobutane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h
Test atmosphere: gas

butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h
Test atmosphere: gas

Skin corrosion/irritation

Product:

Remarks : Irritating to skin.

Components:

Hydrocarbons, C7-C9, isoalkanes:

Species : Rabbit
Assessment : Irritating to skin.
Method : OECD Test Guideline 404
Result : Irritating to skin.

copper:

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C Spray

Version	Revision Date:	Date of last issue: 03.04.2019	Print Date:
7.0	18.12.2019	Date of first issue: 26.05.2015	18.12.2019

Species : Rabbit
Assessment : Irritating to skin.
Result : Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks : Contact with eyes may cause irritation.

Components:

Hydrocarbons, C7-C9, isoalkanes:

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation

copper:

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : yes

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Species : Rabbit
Assessment : Irritating to eyes.
Method : OECD Test Guideline 405
Result : Irritating to eyes.

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

Hydrocarbons, C7-C9, isoalkanes:

Species : Guinea pig
Assessment : Did not cause sensitisation on laboratory animals.
Method : OECD Test Guideline 406
Result : Did not cause sensitisation on laboratory animals.

copper:

Test Type : Maximisation Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C Spray

Version	Revision Date:	Date of last issue: 03.04.2019	Print Date:
7.0	18.12.2019	Date of first issue: 26.05.2015	18.12.2019

Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.
GLP : yes

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Assessment : Does not cause skin sensitisation.
Result : Does not cause skin sensitisation.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

Hydrocarbons, C7-C9, isoalkanes:

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

copper:

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Genotoxicity in vitro : Test Type: Ames test
Result: negative

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Carcinogenicity

Product:

Remarks : No data available

Components:

Hydrocarbons, C7-C9, isoalkanes:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

copper:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C Spray

Version	Revision Date:	Date of last issue: 03.04.2019	Print Date:
7.0	18.12.2019	Date of first issue: 26.05.2015	18.12.2019

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

Components:

Hydrocarbons, C7-C9, isoalkanes:

Reproductive toxicity - Assessment : No toxicity to reproduction
No toxicity to reproduction

copper:

Reproductive toxicity - Assessment : No toxicity to reproduction
No toxicity to reproduction

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Reproductive toxicity - Assessment : No toxicity to reproduction
No toxicity to reproduction

STOT - single exposure

Components:

Hydrocarbons, C7-C9, isoalkanes:

Exposure routes : Inhalation
Target Organs : Central nervous system
Assessment : May cause drowsiness or dizziness.

copper:

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Assessment : The substance or mixture is not classified as specific target

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C Spray

Version	Revision Date:	Date of last issue: 03.04.2019	Print Date:
7.0	18.12.2019	Date of first issue: 26.05.2015	18.12.2019

organ toxicant, single exposure.

STOT - repeated exposure

Components:

copper:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Exposure routes : Ingestion
Assessment : May cause damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

Components:

Hydrocarbons, C7-C9, isoalkanes:

May be fatal if swallowed and enters airways.

copper:

No aspiration toxicity classification

Further information

Product:

Remarks : Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C Spray

Version	Revision Date:	Date of last issue: 03.04.2019	Print Date:
7.0	18.12.2019	Date of first issue: 26.05.2015	18.12.2019

SECTION 12: Ecological information

12.1 Toxicity

Product:

- Toxicity to fish : Remarks: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available
- Toxicity to algae/aquatic plants : Remarks: No data available
- Toxicity to microorganisms : Remarks: No data available

Components:

Hydrocarbons, C7-C9, isoalkanes:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 18,4 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2,4 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 29 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,17 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: Reproduction Test
Method: OECD Test Guideline 211

copper:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0,094 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,0338 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 37,6 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C Spray

Version	Revision Date:	Date of last issue: 03.04.2019	Print Date:
7.0	18.12.2019	Date of first issue: 26.05.2015	18.12.2019

Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 10

Toxicity to fish (Chronic toxicity) : NOEC: 0,021 mg/l
Exposure time: 27 d

M-Factor (Chronic aquatic toxicity) : 1

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 0,1 - 1 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 0,1 - 1 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 0,01 - 0,1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 10

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC50: 1,41 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : 1

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C Spray

Version	Revision Date:	Date of last issue: 03.04.2019	Print Date:
7.0	18.12.2019	Date of first issue: 26.05.2015	18.12.2019

Physico-chemical removability : Remarks: No data available

Components:

Hydrocarbons, C7-C9, isoalkanes:

Biodegradability : Result: Not rapidly biodegradable

copper:

Biodegradability : Remarks: The methods for determining biodegradability are not applicable to inorganic substances.

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: rapidly biodegradable
Biodegradation: 65 %
Exposure time: 28 d
Method: OECD Test Guideline 301D
GLP: yes

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

Components:

Amines, N-C16-C18-alkyl-(evennumbered, C18 unsaturated) propane-1,3-diaminium di[(9Z)-octadec-9-enoate]:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

isobutane:

Partition coefficient: n-octanol/water : log Pow: 2,88
Method: OECD Test Guideline 107

propane:

Partition coefficient: n-octanol/water : log Pow: 2,36

butane:

Partition coefficient: n-octanol/water : log Pow: 2,89
Method: OECD Test Guideline 107

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



WOLFRACOAT C Spray

Version	Revision Date:	Date of last issue: 03.04.2019	Print Date:
7.0	18.12.2019	Date of first issue: 26.05.2015	18.12.2019

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

Components:

copper:

Assessment : Remarks: Not applicable

12.6 Other adverse effects

Product:

Additional ecological information : Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and national regulations.

Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Offer empty spray cans to an established disposal company.
Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied
16 05 04*, gases in pressure containers (including halons)
containing hazardous substances

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



WOLFRACOAT C Spray

Version	Revision Date:	Date of last issue: 03.04.2019	Print Date:
7.0	18.12.2019	Date of first issue: 26.05.2015	18.12.2019

SECTION 14: Transport information

14.1 UN number

ADR : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADR : AEROSOLS
IMDG : AEROSOLS
(Naphtha (petroleum), light alkylate, copper)
IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADR : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADR
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)

IMDG
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)
Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Division 2.1 - Flammable gases

IATA (Passenger)
Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Division 2.1 - Flammable gases

14.5 Environmental hazards

ADR

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



WOLFRACOAT C Spray

Version	Revision Date:	Date of last issue: 03.04.2019	Print Date:
7.0	18.12.2019	Date of first issue: 26.05.2015	18.12.2019

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

P2

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a FLAMMABLE AEROSOLS

E2 ENVIRONMENTAL HAZARDS

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C Spray

Version	Revision Date:	Date of last issue: 03.04.2019	Print Date:
7.0	18.12.2019	Date of first issue: 26.05.2015	18.12.2019

- 18 Liquefied extremely flammable gases (including LPG) and natural gas
- 34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Water contaminating class (Germany) : WGK 3 highly hazardous to water
Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : Total dust:
others: 5,15 %

Inorganic substances in powdered form:
portion Class 3: 1,92 %

Inorganic substances in vapour or gaseous form:
Not applicable
Organic Substances:
others: 92,88 %

Carcinogenic substances:
portion Class 3: 0,05 %

Mutagenic:
others: 0,05 %

Toxic to reproduction:
Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 75,97 %

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



WOLFRACOAT C Spray

Version	Revision Date:	Date of last issue: 03.04.2019	Print Date:
7.0	18.12.2019	Date of first issue: 26.05.2015	18.12.2019

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

- H220 : Extremely flammable gas.
- H225 : Highly flammable liquid and vapour.
- H280 : Contains gas under pressure; may explode if heated.
- H302 : Harmful if swallowed.
- H304 : May be fatal if swallowed and enters airways.
- H315 : Causes skin irritation.
- H319 : Causes serious eye irritation.
- H336 : May cause drowsiness or dizziness.
- H373 : May cause damage to organs through prolonged or repeated exposure if swallowed.
- H400 : Very toxic to aquatic life.
- H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

- Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- Note P : The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260- P262-P301 + P310-P331 shall apply. This note applies only to certain complex oil-derived substances in Part 3.
- Note U (table 3.1) : When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).
- DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.
- DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE

KLÜBER
LUBRICATION

WOLFRACOAT C Spray

Version	Revision Date:	Date of last issue: 03.04.2019	Print Date:
7.0	18.12.2019	Date of first issue: 26.05.2015	18.12.2019

Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Aerosol 1	H222, H229
Skin Irrit. 2	H315
STOT SE 3	H336
Asp. Tox. 1	H304
Aquatic Chronic 2	H411

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Based on product data or assessment
Calculation method

This safety data sheet applies only to products originally packed and labelled by KLÜBER LUBRICATION. The information contained therein may not be reproduced or modified without the express written permission of KLÜBER LUBRICATION. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of our safety data sheets (e.g. as a document for download from the Internet) is not permitted without the express written consent of KLÜBER LUBRICATION. KLÜBER LUBRICATION provides its customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. KLÜBER LUBRICATION provides no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE



WOLFRACOAT C Spray

Version	Revision Date:	Date of last issue: 03.04.2019	Print Date:
7.0	18.12.2019	Date of first issue: 26.05.2015	18.12.2019

the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorised trading partner of KLÜBER LUBRICATION.